

PORTFOLIO BULLETIN

2020-017 | February 28



Phase-Out of some D120h configurations

Following the strict European Regulations on Energy Efficiency, some of the D120h configurations will stop being shipped to the European market by June 1st 2020. Even though it concerns only the European market, it will also affect customer deliveries outside the European market, as all shipments have to transit via NEC warehouse located in the Netherlands.

Phased-Out Configurations

This announcement concerns the following configurations:

Part Number	Description	NOT available in Prophix	
		with 1 or 2 Nodes and 1 CPU	with 1 or 2 Nodes and 2 CPU
N8141-94F	D120h Chassis 2U RAID/SAS 2x2200W		
N8100-2554F	D120h 2U Server Module		
Above chassis and Module combination with the following CPU model			
N8101-1377F	Intel® Xeon® Platinum 8164 (2.00 GHz, 26C/52T, 35.75MB, TDP 150W)	X	
N8101-1376F	Intel® Xeon® Platinum 8160 (2.10 GHz, 24C/48T, 33MB, TDP 150W)	X	
N8101-1375F	Intel® Xeon® Gold 6152 (2.10 GHz, 22C/44T, 30.25MB, TDP 140W)	X	
N8101-1372F	Intel® Xeon® Gold 6138 (2.00 GHz, 20C/40T, 27.50MB, TDP 125W)	X	
N8101-1373F	Intel® Xeon® Gold 6140 (2.30 GHz, 18C/36T, 24.75MB, TDP 140W)	X	
N8101-1369F	Intel® Xeon® Gold 6130 (2.10 GHz, 16C/32T, 22MB, TDP 125W)	X	
N8101-1367F	Intel® Xeon® Gold 5120 (2.20 GHz, 14C/28T, 19.25MB, TDP 105W)	X	X
N8101-1098F	Intel® Xeon® Gold 5118 (2.30 GHz, 12C/24T, 16.50MB, TDP 105W)	X	X
N8101-1097F	Intel® Xeon® Silver 4116 (2.10 GHz, 12C/24T, 16.5MB, TDP 85W)	X	X
N8101-1096F	Intel® Xeon® Silver 4114 (2.20 GHz, 10C/20T, 13.75MB, TDP 85W)	X	X
N8101-1095F	Intel® Xeon® Silver 4110 (2.10 GHz, 8C/16T, 11MB, TDP 85W)	X	X
N8101-1094F	Intel® Xeon® Silver 4108 (1.80 GHz, 8C/16T, 11MB, TDP 85W)	X	X

Part Number	Description	<u>NOT</u> available in Prophix	
		with 2 Nodes and 1 CPU	with 2 Nodes and 2 CPU
N8101-1093F	Intel® Xeon® Bronze 3106 (1.70 GHz, 8C/8T, 11MB, TDP 85W)	X	X
N8101-1092F	Intel® Xeon® Bronze 3104 (1.70 GHz, 6C/6T, 8.25MB, TDP 85W)	X	X
N8101-1374F	Intel® Xeon® Gold 6142 (2.60 GHz, 16C/32T, 22MB, TDP 150W)	X	
N8101-1370F	Intel® Xeon® Gold 6132 (2.60 GHz, 14C/28T, 19.25MB, TDP 140W)	X	
N8101-1371F	Intel® Xeon® Gold 6134 (3.20 GHz, 8C/16T, 24.75MB, TDP 130W)	X	
N8101-1368F	Intel® Xeon® Gold 5122 (3.60 GHz, 4C/8T, 16.50MB, TDP 105W)	X	
N8101-1378F	Intel® Xeon® Platinum 8160M (2.10 GHz, 24C/48T, 33MB, TDP 150W)	X	

Or

Part Number	Description	<u>NOT</u> available in Prophix	
		with 1,2,3 or 4 Nodes and 1 or 2 CPU	
N8141-93F	D120h Chassis 1U RAID/SAS 2x2200W		
N8100-2553F	D120h 1U Server Module		
Above chassis and Module combination with the following CPU model			
N8101-1092F	Intel® Xeon® Bronze 3104 (1.70 GHz, 6C/6T, 8.25MB, TDP 85W)	X	

Ordering

Prophix configurations rules has been amended accordingly. All configurations related to the D120h will also have to be confirmed by the Product Manager before the order can be accepted.